

Material Safety Data Sheet

EXTREME WHITE GEL

Section 1 - Identification of the Substance/Preparation and of the Company/Undertaking

Product Name: EXTREME WHITE GEL
 Chemical Name: N/A

| | |
|---------------------|-----------|
| MSDS Approval Date: | 6/20/2008 |
| MSDS Prepared by: | JRR |

Family: UV GELS

Manufacturer: ABC International Sp. z o.o.
 Ul. Odolańska 10 Warszawa 02-560
 Emergency Phone Numbers: (0048)42 631 47 24
 Information Contacts: (0048)228800455

Product Use: NAIL GEL

Product#: various

Section 2 - Composition/Information on Ingredients

| Chemical Identity | CAS# | EINECS# | INCI Name | Exposure OSHA TWA/STEL | Limits ACGIH TWA/STEL | Carcinogen IARC/NTP/OSHA | % |
|-------------------------------------|------------|-----------|-------------------------------------|------------------------------|-----------------------------|-----------------------------|-------|
| Polyurethane Acrylate Oligomer | Exempt | N/E | Di-Hema Trimethylhexyl Dicarbamate* | N/E | N/E | Not Listed | 75-85 |
| Tetraethylene glycol Dimethacrylate | 109-17-1 | 203-653-1 | PEG-4 Dimethacrylate | N/E | N/E | Not Listed | 10-15 |
| Hydroxycyclohexyl phenyl ketone | 947-19-3 | 213-426-9 | Hydroxycyclohexyl phenyl ketone | N/E | N/E | Not Listed | 1-3 |
| Titanium Dioxide | 13463-67-7 | 236-675-5 | Titanium Dioxide/CI77891 | 15 mg/m3 | 10 mg/m3 | 3/no/no | 0-5 |
| D&C Violet #2 | 81-48-1 | 201-353-5 | Violet 2/CI60725 | N/E | N/E | Not Listed | 0-1 |
| Silicon Dioxide* | 60676-86-0 | 262-373-8 | Silica | N/E | N/E | Not Listed | 0-1 |

N/E - None Established
 N/R - Not Reviewed

N/DA - No Data Available
 N/A - Not Applicable

* See section 16

Hazard Symbols: Xi Risk Phrases: R22, R36/38, R43 Safety Phrases: S18, S24/25, S36/37, S38

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

This information may be based on findings from related or similar materials.

- May be slightly toxic.
- May cause moderate skin injury (reddening & swelling).
- May cause chemical burn in eye.
- Suspect respiratory tract irritation hazard.

Potential Health Effects, Signs and Symptoms of Exposure:

| | |
|------------------------|---|
| Primary Route of Entry | No specific information is available for this product. Although, this product opposes only slight irritation concern with all routes of entry. |
| Eye | No specific information available. Contains materials that are essentially nonirritating, but contact may cause slight transient irritation. |
| Skin | No specific information available. Contains materials that may cause moderate skin injury (reddening and swelling) and/or sensitization. Prolonged contact may cause blister formation (burns). Since irritation may not occur immediately, contact can go unnoticed. |
| Ingestion | No specific information available. Contains materials that may be practically nontoxic. |
| Inhalation | No specific information available. Low volatility makes vapor inhalation unlikely. Aerosol can be irritating. |
| Sub-Chronic Effects | No specific information available. Limited tests showed no evidence of teratogenicity in animals. A lifetime skin painting study with mice showed no evidence of carcinogenicity. |

NOTE: Refer to Section 11, Toxicological Information for Details

Section 4 - First Aid Measures

| | |
|--------------------------|---|
| First Aid for Eye | Flush with plenty of water for 15 minutes and retract eyelids often. Seek medical attention immediately. |
| First Aid for Skin | Remove contaminated clothing and wash contact area with soap and water for 15 minutes. |
| First Aid for Inhalation | In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention. |
| First Aid for Ingestion | If appreciable quantities are swallowed, seek medical attention. |

Section 5 - Fire Fighting Measures

| Flash Point (°F/°C) | Flammable Limit (vol%) | Auto-ignition Temperature (vol%) |
|---------------------------|---------------------------|-------------------------------------|
| > 212°F/100°C. Setofflash | No Data | No Data |

| | |
|-----------------------------|--|
| Method: | |
| Extinguishing Media: | Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires. |
| Fire Fighting Instructions: | Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion exists. |
| Unusual Hazards: | High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers. Avoid the use of a stream of water to control fires since frothing can occur. |

Section 6 - Accidental Release Measures

| | |
|-----------------------------|---|
| Spill or Release Procedures | Spontaneous polymerization can occur. Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Dike and recover large spills. Soak up small spills with inert solids (such as vermiculite, clay) and sweep/shovel into disposal container. Wash spill area with strong detergent and water solution; rinse with water, but minimize water use during clean-up. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways. |
|-----------------------------|---|

Section 7 - Handling and Storage

| | |
|------------------|--|
| Handling | Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid prolonged exposure to light. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential. |
| Storage | Most acrylic monomers have low viscosities, thus only needing room temperature conditions to facilitate proper pouring techniques. However, viscous type gels such as these may require heating to facilitate proper pouring techniques. To ensure that this happens, product may be heated to 60°C/140°F for not more than 24 hours. Do NOT use localized heat sources such as band heaters to heat/melt product. Do NOT use steam. Hot boxes or hot rooms are recommended for heating/melting material. The hot box and/or room should only be set to a maximum temperature of 60°C/140°F. Do not overheat, this may compromise product effectiveness and should be avoided. Refrain from multiple reheatings of product, this will also diminishing the quality of the product. |
| Explosion Hazard | Product is extremely light sensitive. If exposed to natural light or UV light, material will cure very quickly. Store in a cool, dry place, away from heat and all types of light. Store at temperatures below 100°F/38°C but above the product's freezing point. If no freezing point is given, keep above 32°F/0°C at all times. |
| | High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers. |

Section 8 - Exposure Controls / Personal Protective Equipment

| | |
|-------------------------------|--|
| Engineering Controls | Local exhaust recommended to control exposure which may result from operations generating aerosols and hot operations generating vapors. |
| Personal Protective Equipment | |
| General | To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC. |
| Eye/ Face Protection | Wear chemical splash goggles. |
| Skin Protection | Wear impervious gloves (Neoprene). |
| Respiratory Protection | A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the |

Material Safety Data Sheet

EXTREME WHITE GEL

respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

Section 9 - Physical and Chemical Properties

| | | | | | | | |
|---|---|---|--|-----------------------------|---------------------------------|---------------------|---|
| Appearance Clear, viscous liquid | Odor & Odor Threshold characteristic acrylate odor | pH NA | Specific Gravity (H2O=1) : 1.15 | Viscosity N/DA | % Volatile By Volume : < 0.5 | | |
| Boiling Point/ Freezing Point N/A | Decomposition Temperature N/A | Octanol/Water Partitioning Coefficient Log Po/w N/A | Vapor Pressure: (mm Hg) @ 20 C : < 0.01 | Vapor Density No Data | Evaporation Rate No Data | Ignition No Data | Solubility In Water (20°C) Insoluble |
| Flash Point (°F/°C) > 212°F/100sC Setaflash | Flammable Limit (vol%) No Data | Auto-ignition Temperature (vol%) No Data | | | | | |

Section 10 - Stability and Reactivity

| | |
|---|---|
| <p>Stability Normally Stable</p> <p>Hazardous Decomposition Products: Fumes produced when heated to decomposition may include: carbon monoxide, carbon dioxide.</p> <p>Conditions to Avoid: Storage >100°F/38°C , exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.</p> | <p>Incompatibility (Materials to Avoid): Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and string bases.</p> <p>Hazardous Polymerization: May occur -- Uncontrolled polymerization may cause rapid evolution of Heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.</p> |
|---|---|

Section 11 - Toxicological Information

| | | | | |
|--|---|---|---|--|
| Acute Oral Toxicity No information available | Acute Dermal Toxicity No information available | Acute Inhalation Toxicity No information available | Irritation - skin No information available | Irritation - Eye No information available |
| <p>Since this product contains a very low concentration of active components, the primary toxicological information is derived from the oligomers. Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.</p> | | | | |
| Sensitization N/DA | Mutagenicity N/DA | Sub-chronic Toxicity N/DA | | |

Section 12 - Ecological Information

Ecotoxicological Information

| | | | | |
|-----------------------------------|--|------------------------------------|--------------------------|-------------------------------------|
| Acute Toxicity to Fish N/DA | Acute Toxicity to Invertebrates N/DA | Acute Toxicity to Algae N/DA | Bioconcentration N/DA | Toxicity to Sewage Bacteria N/DA |
|-----------------------------------|--|------------------------------------|--------------------------|-------------------------------------|

Chemical Fate Information

| | |
|------------------------|------|
| Biodegradability | N/DA |
| Chemical Oxygen Demand | N/DA |

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil

Section 13 - Disposable Considerations

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the generators responsibility to determine what is classified as a hazardous waste. Comply with all federal, state, and local regulations.
Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

Section 14 - Transport Information

| | |
|------------------|--|
| DOT (49 CFR 172) | |
|------------------|--|

Material Safety Data Sheet

EXTREME WHITE GEL

| | |
|---|------------------------|
| Proper Shipping Name: | Non-Regulated Material |
| Identification Number: | N/A |
| Marine Pollutant: | No |
| Special Provisions: | N/A |
| Emergency Response Guidebook (ERG) #: | N/A |
| IATA (DGR): | |
| Proper Shipping Name: | Non-Regulated Material |
| Class or Division: | N/A |
| UN or ID Number: | N/A |
| Packaging Instructions: | |
| Emergency Response Guidance (ICAO)#: | |
| IMO (IMDG): | |
| Proper Shipping Name: | Non-Regulated Material |
| Class or Division: | N/A |
| UN or ID Number: | N/A |
| Special Provisions & Stowage/Segregation: | None |
| Emergency Schedule (EmS)#: | |
| Other Information: | Flash point > 100°C |

Section 15 - Regulatory Information

US Federal Regulations

| | |
|-------------------------------------|--|
| Clean Air Act: HAP/ODS | This product contains the following hazardous air pollutants (HAP and ODS's), as defined by the U.S. Clean Air Act: <ul style="list-style-type: none"> • NONE This product does not contain any ODS's (Ozone Depleting Substances). |
| Clean Water Act: Priority Pollutant | This product contains no chemicals listed under the U. S. Clean Water Act Priority Pollutant List. |
| FDA: Food Packaging Status | This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food additive. |
| Occupational Safety and Health Act | This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its hazards are: <ul style="list-style-type: none"> • Immediate (acute) health hazard • Delayed (chronic) health hazard • Reactive hazard |
| RCRA | This product is not considered to be a hazardous waste under RCRA (40 CFR 261). |
| SARA Title III: Section 302 (TPQ) | This product contains the following chemicals regulated under Sec. 302 as extremely hazardous substances that carry a TPQ. <ul style="list-style-type: none"> • NONE |
| SARA Title III: Section 302 (RQ) | This product contains the following chemicals regulated under Section 302 as extremely hazardous chemical for emergency release notification ("CERCLA" List). <ul style="list-style-type: none"> • NONE |
| SARA Title III: Section 311-312: | This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: <ul style="list-style-type: none"> • Immediate (acute) health hazard • Delayed (chronic) health hazard • Reactive hazard |
| SARA Title III: Section 313: | This product contains the following chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: <ul style="list-style-type: none"> • NONE |
| TSCA Section 8(b): Inventory: | This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements. |
| TSCA Significant New Use Rule: | None of the chemicals listed have a SNUR under TSCA. |


State Regulations

Material Safety Data Sheet

EXTREME WHITE GEL



| | |
|--------------------------------------|--|
| CA Right-to-Know Law: | NONE |
| California No Significant Risk Rule: | NONE |
| MA Right-to-Know Law: | Titanium Dioxide CAS #13463-67-7, Silicon Dioxide, CAS#7631-86-9. |
| NJ Right-to-Know Law: | Titanium Dioxide CAS #13463-67-7, Silicon Dioxide, CAS#7631-86-9. |
| PA Right-to-Know Law: | Titanium Dioxide CAS #13463-67-7, Silicon Dioxide, CAS#7631-86-9. |
| FL Right-to-Know Law: | Silicon Dioxide, CAS#7631-86-9. |
| MN Right-to-Know Law: | Titanium Dioxide CAS #13463-67-7, Silicone Dioxide, CAS#7631-86-9. |

International Regulations

| | |
|--|--|
| CDSL: Canadian Inventory (on Canadian Transitional List) | Tetraethylene glycol dimethacrylate, CAS# 109-17-1 is not on the DSL List. WHMIS = n/da Hydroxycyclohexyl phenyl ketone CAS# 947-19-3 is on the DSL list. WHMIS = n/da Titanium dioxide CAS # 13463-67-7 is on the DSL list. WHMIS = n/da Silicon Dioxide, CAS#7631-86-9 is on the DSL list. WHMIS = n/da |
| EINECS: European Inventory:  | <ul style="list-style-type: none"> HAZARD SYMBOLS: Xi: Irritant RISK PHRASES: R22: Harmful if swallowed, R36/38: Irritating to eyes and skin R43: May cause sensitization by skin contact. SAFETY PHRASES: S18: Handle and open container with care, S24/25: avoid contact with skin and eyes, S36/37: Wear suitable protective clothing and gloves, S38: in case of insufficient ventilation, wear suitable respiratory equipment. |

Section 16 - Other Information

Hazard Rating System (Pictograms)

| | | | |
|-------|--|-------|--|
| NFPA: |  <p>Health → 2 ← Flammability 1 ← Reactivity 1</p> | HMIS: |  <p>2 Health 1 Flammability 1 Reactivity</p> |
|-------|--|-------|--|

* OSHA PEL for nuisance dust: 15 mg/m³ (total dust)
5 mg/m³ (respirable dust)
ACGIH PEL for nuisance dust: 10 mg/m³

| | |
|--------------------------------------|---------------------------|
| Revised Sections since Last Version: | 06/20/2008 Initial Issue. |
|--------------------------------------|---------------------------|

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (0048)42 631 47 24.